

## HAND DRYER

## SENSOR OPERATED

JET



## Reference: 11.113 AISI 304 stainless steel satin

COMPONENTS & MATERIALS	TECHNICAL SPECIFICATIONS
·Overall stainless steel food grade 304 satin finish.	• Material AISI 304 stainless steel
·High speed self-developed brushless motor.	• Cover thickness 1.0 mm thick
·3 IR sensors in both sides for automatic hands	· Voltage/Frequency AC220V, 50/60Hz
detection.	· <b>r.p.m.</b> 19000-20000
·HEPA filter which avoids the entry of the tiny	• Total power 2200W
particles.	• Motor power 700W
·Internal tank to collect the water and avoid a mess.	· Heating element power 1500W
•Designed for high traffic bathroom and continuous	• Air velocity 90-95m/s
use.	• Air temperature 20-40°C
·Easy maintenance.	• Noice level <68dB
Dimension: 625 high x 290 wide x 198 deep mm.	• Protection level IP34
·Warranty: 3 years.	• Drying time 5-10s
CERTIFICATE	TECHNICAL DRAWING
CE	

Fax: +86 571 888 685 71

## FEATURES

·Overall stainless steel food grade 304, including inner structures & install screws.

·No openings or cracks on the surface, easy to clean dirt, no chance for bacteria survive.

·No fear of fire, burning cigarette butts. Scratch can be repaired.

·Sealing material CR4305.







•Adopting a complete closed structure to protect brushless motor and stainless steel rotor, last up to 10 years.





·Washable with water. Disinfect with disinfectant, ultraviolet rays and hot water.





 $\cdot Use$  vacuum cleaner and air blower (colder) to clean HEPA filter.

·Outer filter can be washed for repeated use.

·Warranty: 3 years.





Tel: +86 571 888 685 70 Fax: +86 571 888 685 71 hotec@cnhotec.com www.cnhotec.com