

SENSOR OPERATED

JET



Reference: 11.107  
ABS

### COMPONENTS & MATERIALS

- One-piece cover.
- High speed brush motor.
- Strong, vandal proof and build without edges.
- Universal brush motor incorporating a safety thermal cut-off.
- Element incorporates a safety thermal cut-off.
- Double Sterilization-UV Light kills microbial bacteria in air. HEPA Filtration System proven to remove 99.9% of potentially present bacteria at 0.3 microns from the air.
- Easy maintenance.
- Dimension: 632 high x 300 wide x 167 deep mm.

### TECHNICAL SPECIFICATIONS

|                                |                     |
|--------------------------------|---------------------|
| · <b>Material</b>              | ABS                 |
| · <b>Cover thickness</b>       | 3.0 mm thick        |
| · <b>Voltage/Frequency</b>     | AC220-240V, 50/60Hz |
| · <b>Consumption</b>           | 6.2A                |
| · <b>Electrical Isolation</b>  | CLASS II            |
| · <b>Total power</b>           | max.1350W           |
| · <b>Motor power</b>           | max.1000W           |
| · <b>Heating element power</b> | max.350W            |
| · <b>Air velocity</b>          | 90m/s               |
| · <b>Air temperature</b>       | 20-40°C             |
| · <b>Noise level</b>           | 69dB                |
| · <b>Protection level</b>      | IP34                |
| · <b>Drying time</b>           | 7-10s               |

### CERTIFICATE



### TECHNICAL DRAWING

